

用途 Application:

- 产品主要用于农业，如养殖业料线等 Mainly used for agriculture, such as manufacture of blades for screw conveyer

表面状态 Surface coating:

- 光面 Bright

特点 Characteristics:

- 供货状态: 油淬火态 Delivery condition: Oil quenched
- 材料硬度波动小，疲劳寿命稳定、耐磨性好 Good hardness uniformity, stable fatigue life, good wear resistance

包装方式 Packing types:

- 脱件 Coil

弹簧料线用扁丝 FLATTENED WIRES FOR SPIRAL BLADE



使用注意事项 Remarks during use and handling:

- 运输过程中应轻提轻放，防止撞击损坏钢丝，防潮并严禁淋雨，钢丝应储存在干燥的室内
During transportation, handle with care, avoid bumping and damaging the steel wires. Moisture and rain prohibited. Steel wires must be stored in dry warehouse.
- 使用时应注意钢丝放线方向，并注意放线张力的一致性
Pay attention to the direction of steel wire when pay-off. Be sure the spool is rotating freely as to achieve identical tension.
- 如多次使用，剩余钢丝必须及时重新包裹，防止钢丝表面氧化变质
If the single unit package can not be used up, the remained wire should be repacked to avoid oxidizing.



弹簧料线用扁丝 典型参数 Typical parameters

材质 Material	典型规格 Typical size h×b(mm)	硬度 Hardness	热处理状态 Heat treatment	包装重量 Coil weight
57B	6.00×12.00	HRC 36~42	油淬火Oil quenched	>500 kg/coil卷
65Mn	5.00×14.00	HRC 36~42	油淬火Oil quenched	>500 kg/coil卷

规格范围: 厚度 (h) (4.00~6.50) mm; 宽度 (b) (8.00~16.50) mm。
Dimension range: thickness (h) (4.00~6.50) mm; width (b) (8.00~16.50) mm.
产品标准: 按客户要求生产。
Standard: In accordance with customers' requests.