

用途 Application:

- 产品主要用于工业模具等领域，如汽车模具、玩具模具、五金模具等 Mainly used for Industrial mould, such as manufacture of springs for automobile mould, toy mould, hardware mould

表面状态 Surface Coating:

- 光面 Bright

特点 Characteristics:

- 供货状态：油淬火态 Delivery condition: oil quenched
- 可以按照日标、美标、欧标生产，疲劳寿命与进口产品相当 Produced according to JIS, ASTM and EN standards, fatigue life is equivalent to the imported products

包装方式 Packing types:

- 脱件 Coil

模具簧用异型钢丝 SHAPED WIRES FOR MOULD SPRING



使用注意事项 Remarks during use and handling:

- 运输过程中应轻提轻放，防止撞击损坏钢丝，防潮并严禁淋雨，钢丝应储存在干燥的室内

During transportation, handle with care, avoid bumping and damaging the steel wires. Moisture and rain prohibited. Steel wires must be stored in dry warehouse.

- 使用时应注意钢丝放线方向，并注意放线张力的一致性

Pay attention to the direction of steel wire when pay-off. Be sure the spool is rotating freely as to achieve identical tension.

- 如多次使用，剩余钢丝必须及时重新包裹，防止钢丝表面氧化变质

If the single unit package can not be used up, the remained wire should be repacked to avoid oxidizing.



模具簧用异型钢丝 典型参数 Typical parameters

材质 Material	典型规格 Typical size h × b(mm)	硬度 Hardness	交货状态 Delivery condition	包装重量 Coil weight
55SiCr	(1.54,1.28) × 3.65	HRC 45~50	油淬火Oil quenched	>200 kg/coil卷
55SiCr	(4.65,3.74) × 4.60	HRC 45~50	油淬火Oil quenched	>500 kg/coil卷

规格范围：从6系列到60系列。
Spring dimension range: from 6 series to 60 series.
产品标准：按客户要求生产。
Standard: In accordance with customers' requests.